

Metal cylindrical shape inductive sensors **LR18X** series



Features

- ◆ Extended sensing distance;
- ◆ ASIC design, safe and reliable;
- ◆ Perfect choice for metallic target detection;




Part number

NPN NO	LR18XCF12DNOY	LR18XCN20DNOY	PNP NO	LR18XCF12DPOY	LR18XCN20DPOY
NPN NC	LR18XCF12DNCY	LR18XCN20DNCY	PNP NC	LR18XCF12DPCY	LR18XCN20DPCY

Technical specifications

Mounting	Quasi -flush	Non-flush	Current consumption	≤15mA
Rated distance [Sn]	12mm	20mm	Circuit protection	Short-circuit, overload and reverse polarity
Assured distance [Sa]	0...9.6mm	0...16mm	Output indicator	Yellow LED
Dimensions	M18*61.5mm	M18*73.5 mm	Ambient temperature	-25°C...70°C
Output	NO/NC(depends on part number)		Ambient humidity	35-95%RH
Supply voltage	10...30 VDC		Switching frequency [F]	300Hz 150Hz
Standard target	Fe 36*36*1tFe 60*60*1t		Voltage withstand	1000V/AC 50/60Hz 60S
Switch-point drifts[%/Sr]	≤ ± 10%		Insulation resistance	≥50MΩ (500VDC)
Hysteresis range [%/Sr]	1...20%		Vibration resistance	10...50Hz (1.5mm)
Repeat accuracy [R]	≤3%		Degree of protection	IP67
Load current	≤200mA		Housing material	Nickel-copper alloy
Residual voltage	≤2.5V		Connection type	2m PVC cable

Dimensions



Wiring diagram

